



Goodyear Wrangler RT/S

Light Truck/SUV Tire

Features and Benefits

Goodyear's smooth riding all-weather radial is capable of all-terrain duties. The computer-optimized tread design makes this Wrangler versatile. It delivers comfortable, dependable all-weather traction on the highway and is ready for off-road duty when called upon.

Premium Tread Width

Delivers better ride quality, handling and traction.

Deep circumferential grooves

Help maintain wet and snow traction by evacuating water and slush to resist hydroplaning.

Continuous tread block design

Delivers smooth highway ride and good off road traction.

Siping throughout the tread

Adds extra gripping edges for enhanced wet and snow traction.

Two steel belts

Ensure rugged penetration resistance, durability and better handling.

Long wearing tread compound

Delivers better value and is also designed to maximize highway traction in all weather conditions as well as off-road.

Contemporary appearance

Popular OE styling RBL with sidewall and rugged shoulder design.



Illustration typifies tire construction based on information provided by the manufacturer. Features are not to be interpreted as precisely sized or scaled.

Goodyear Wrangler RT/S Performance Ratings



Comfort- Minimizes noise, harshness and vibration felt by driver and passengers.

Handling- Handles curves, turns and stops of everyday driving and provides an "on-center" feel; resists tracking.

Tread Wear- Delivers guaranteed wear.

Traction (highway)- Provides highway all-season traction.

Traction (off-road)- Deliver off-road traction in mud, rocks, gravel and sand.

Appearance- Tire's curb appeal adds to the look of the vehicle.

DTC Recommended Value- Blends price and performance evaluation.

Light Truck/SUV Overview

The Light Truck and SUV market may be broken into three classes of tires: highway (Highway Tread or HT), combination on-road/off-road (All Terrain or AT) and off-road (Mud Terrain or MT).

Highway or HT tires include rib-type commercial tires and newer all-season tire designs. The later offer a rugged truck look and heavier load carrying capacities, but essentially perform like a passenger all-season tire. Michelin's LTX MS and the new Pathfinder Luxury SUV are good examples. This is the fastest growing market segment and new designs are announced almost monthly.

Combination or AT tires offer dual role highway and off-road service, and essentially compromise performance on both sides. They are noisier on the highway than HTs and don't provide the traction of a MT when off-road. However, for the customer who consistently uses their vehicle on and

off road , the AT strikes an acceptable balance.

BFGoodrich's All-Terrain T/A KO and our Pathfinder ATR are good example of this tire.

Finally, **off-road** or MT tires offer the best traction in the mud, sand and rock, but sacrifice on road performance. You can usually hear a vehicle equipped with MT tires a hundred feet away as it drives down the highway. Goodyear's Wrangler MT and BFGoodrich's Mud-Terrain T/A are good examples of this tire.

Specifications

Tire Size	Service Description	Sidewall Style	Approved Rim Width	Overall Diameter	Section Width	Max. Load LBS.
31X10.50R15/C		OWL	7.0- 9.0	30.5	10.5	2,270 @ 50
LT215/85R16/E		OWL	5.5- 7.0	30.3	8.5	2,680 @ 80
LT235/85R16/E		BSL	6.0- 7.0	31.7	9.2	3,042 @ 80
LT245/75R16/D		OWL	6.5- 7.5	30.4	9.7	2,623 @ 65
LT245/75R16/E		BSL	6.5- 7.5	30.4	9.7	3,042 @ 80
LT245/75R16/E		OWL	6.5- 7.5	30.4	9.7	3,042 @ 80
LT265/75R16/E	123R	BSL	7.0- 8.0	31.6	10.5	3,415 @ 80
P205/75R15/SL	097S	OWL	5.0- 7.0	27.1	7.9	1,598 @ 35
P205/75R15/SL	97S	BSL	5.0- 7.0	27.1	7.9	1,598 @ 35
P215/75R15/SL	100S	OWL	5.5- 7.0	27.6	8.5	1,742 @ 35
P215/75R15/SL	100S	VSB	5.5- 7.0	27.6	8.5	1,742 @ 35
P225/75R15/SL		OWL	6.0- 7.5	28.3	8.7	1,874 @ 35
P235/70R15/SL	102S	OWL	6.0- 8.0	27.9	9.4	1,896 @ 35
P235/70R16/SL	104S	OWL	6.0- 8.0	28.9	9.4	1,984 @ 35
P235/75R15/SL	105S	OWL	6.0- 8.0	28.8	9.2	2,028 @ 35
P235/75R15/SL	105S	OWL	6.0- 8.0	28.8	9.2	2,028 @ 35
P235/75R15/SL	105S	BSL	6.0- 8.5	28.8	9.2	1,844 @ 35
P235/75R15/XL	108S	OWL	6.0- 8.0	28.8	9.2	2,183 @ 41
P245/75R16/SL	109S	OWL	6.5- 8.0	30.4	9.7	2,271 @ 35
P245/75R16/SL	109S	BSL	6.5- 8.0	30.4	9.7	2,271 @ 35
P255/70R16/SL	109S	OWL	6.5- 8.5	30	10.2	2,271 @ 35
P265/70R16/SL	111S		7.0- 9.0	30.6	10.7	2,403 @ 35
P265/70R17/SL	113S	OWL	7.0- 9.0	31.6	10.7	2,535 @ 35
P265/75R15			7.0- 9.0	30.6	10.5	2,469 @ 35
P265/75R15/SL		BSL	7.0- 9.0	30.6	10.5	2,469 @ 35
P265/75R16/SL	114S	OWL	7.0- 9.0	31.6	10.5	2,601 @ 35
P265/75R16/SL	114H	BSL	7.0- 9.0	31.6	10.5	2,601 @ 35

Sizes listed represent the latest information provided by the manufacturer. The sizes marketed and available will vary by region.